

For protection against overpressure and vacuum in gases and liquids

Flat rupture discs from REMBE[®] offer you fragmentation-free opening across the full width of the vent.


They can be produced in virtually any size, for extremely low pressures from 15 mbar and with very low burst tolerances.

FLAT RUPTURE DISCS

For protection against overpressure and vacuum, e.g. in storage vessels and low pressure systems. Also suitable as a secondary safety device alongside breather valves. This rupture disc is designed to work at standard operating ratios of up to 50%* of the min. response pressure. It is installed directly between flanges and due to its half holes is suitable for all flange systems. A wide range of materials can be used as seals.

Your advantages

- **Requires less space than safety valves** due to the lower installation height.
- Available for all flanges and in any nominal width.
- No holder required for installation.



* Depending on the specific application

Technical data								
NPS [in]	DN [mm]	pressure cl PN	ass ANSI	B [mm]	A [mm]	BC [mm]	n [mm]	D [mm]
3/4"	20	16-40	300-1500	22	73	75	4.0	14
1"	25	6-40	150-900	29	76	80	4.0	16
1½"	40	6-40	150-900	43	95	100	4.0	18
2"	50	16-40	150-300	55	107	120	4.0	20
3"	80	6-64	150-900	83	165	156	8.0	24
4"	100	16-64	150-600	107	190	186	8.0	24
6"	150	16-40	150-300	160	247	244	8.0	26
8"	200	6-10	150-300	208	276	280	8.0	18
10"	250	6-10	150-300	261	315	-	-	-
12"	300	6-10	150-300	310	370	-	-	-
14"	350	6-10	150-300	342	420	-	-	-
16"	400	6-10	150-300	393	473	-	-	-
18"	450	6-10	150-300	465	528	-	-	-
20"	500	6-10	150-300	494	575	-	-	-
24"	600	6-10	150-300	596	675	-	-	-
28"	700	6-10	150-300	697	780	-	-	-
30"	750	6-10	150-300	762	876	-	-	-
32"	800	6-10	150-300	799	885	-	-	-
36"	900	6-10	150-300	900	985	-	-	-
40"	1000	6-10	150-300	1002	1085	-	-	-

Different sizes, pressure classes, temperatures, materials and fittings available on request.

You can find detailed information and contact details for enquiries relating to flat rupture discs at www.rembe.de. Or just give us a call: T +49 2961 7405-0, info@rembe.de.

You can find appropriate rupture disc holders and signalling devices from page 32.



7

Técnica Hansa - Marchant Pereira 540 Providencia Santiago, Chile. Teléfono: (+56 2) 2204 5348